



A-151 SOLVENT DEGREASER

The quick penetrating action of A-151 works its way into hard to reach areas, degreasing parts and equipment thoroughly with no need to disassemble equipment to be cleaned.



FEATURES

- NSF® Registered C1 # 059811 (Aerosol); # 059812 (Bulk)
- Controlled evaporation
- Ideal for parts washers, dip tanks, and ultrasonic cleaners
- Contains no chlorinated solvents
- Removes oil, grease and other contaminants
- Non-conductive, low odor
- VOC compliant in all 50 states
- High flash point 158°F (70°C)



SPECIFICATIONS AND APPROVALS

- Airbus ABR 9-0140 Type I
- ASTM F-945
- Boeing D6-17487 Rev. P
- Embraer EMB 120 Brasilia C.P.M.-120/1181 Type B-1
- Honda Corp.
- Kimberly-Clark
- Learjet LES1239J
- McDonnell Douglas CSD #1
- NSF® International
- Xerox

PACKAGE SIZES

Net Contents

15 wt.oz. / 425 g/ 498 ml aerosol
 5 gal. (18.93 L)
 55 gal. (208 L)

Part No.

04320
 04305
 04355

APPLICATIONS

- Aircraft engine components
- Bearings
- Cables
- Chains
- Controls
- Dip tanks
- Electric Motors
- Gauges
- Gears
- Heavy Equipment
- High-voltage cable connections
- Parts washers
- Ultrasonic Cleaners



A-151

SOLVENT DEGREASER

PROPERTIES

Appearance/physical state	Liquid	Vapor density	6.1 (air = 1)
Color	Clear, water-white	Solubility(ies)	Not soluble in water
Odor	Characteristic	Partition coefficient (n-octanol/water)	>1
Dielectric strength	36,000 volts	Auto-ignition temperature	>381.2 °F (>194 °C)
Boiling point	>408 °F (>209 °C)	Viscosity	<3 mm ² /s @ 25 °C
Flash point	158 °F (70 °C) TCC	Heat of combustion	>30 kJ/g
Evaporation rate	<0.1 BuAc	Specific gravity	0.84 - 0.86 @ 20 °C
Flammability limit: Upper Lower	0.6% (estimated) 20.4% (estimated)	VOC (weight%)	0% per U.S. State and Federal Consumer Product Regulations
Vapor pressure	<0.1 mm Hg @ 20 °C	Propellant Type (aerosol)	Carbon dioxide

HANDLING

DO NOT spray into or around ignition sources. After handling, always wash hands thoroughly with soap and water. Use only with adequate ventilation. Avoid breathing vapors or spray mists. Avoid contact with eyes, skin, and clothing. Ground and bond containers before transferring materials.

STORAGE

Keep container in a cool, dry, well-ventilated area. Avoid all sources of ignition (spark or flame). Store below 120 °F.

DIRECTIONS

AEROSOL: Spray metal parts and equipment and let LPS® A-151 Solvent Degrease run off. Air dry or wipe with an absorbent cloth for faster drying. Test rubber and plastic surfaces for compatibility. Safe to use on most surfaces, although prolonged contact with aircraft transparencies should be avoided.

BULK: Apply and let LPS® A-151 Solvent Degreaser run off. Air dry or wipe with an absorbent cloth for faster drying. Test rubber and plastic surfaces for compatibility.

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE : WWW.LPSLABS.COM

LPS® Laboratories • An Illinois Tool Works Company
4647 Hugh Howell Road • Tucker, GA 30084 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899
Internet Web Site: www.lpslabs.com

©2013 LPS® Laboratories • LPS® is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #TDS_04320 • Rev. 8/2013